




# Administration = Information + Services


- Rhapsody supports several Information systems
  - NIS, DNS, LDAP, local files
- Primary Information system is NetInfo
- These systems just store data various servers do the real work
- Today's presentation from the developer's point of view



#### **NetInfo Overview**

- A reliable distributed data store for network and system administration
- Contains records describing users, printers, mailing lists, and etc.
- Also stores configuration settings, server and resource locations

# A Three-Level Hierarchy









## NetInfo Namespace

- A tree-structured namespace
- A hierarchy of domains
- Each domain stores a hierarchy of directories
- Directories are data bearing objects

### **Domains and Directories**







Directory Hierarchy


Property List

zorba name: realname: Zorba The Geek pg5nMizy/WeOs passwd: uid: 12345 gid: 123 home: /Users/zorba shell: /bin/csh zorba writers passwd:



## **Storing Data**

- A directory contains a list of properties
- Each property has one ASCII key and any number of ASCII values
- Directories in certain categories (e.g., users) have required properties
- New properties may be added on the fly



#### Access Control

- NetInfo is world-readable
- All data is writable by "root" user
- Write ACLs per directory and per property



## Reliability


- Each domain has a master server
- A domain may have any number of clone servers
- Write operations always go to the master
- Several master/clone synchronization mechanisms
- Clients automatically reconnect in case of failure



#### **NetInfo Clients**

- Most common lookups go through the System Library
- System Library uses lookupd to find things
- lookupd is the system's main NetInfo client
- Any program may be a NetInfo client

# System Look-up Path





# lookupd

- System's "Information Clearinghouse"
- Client of NetInfo, NIS, DNS, etc.
- Cache for improved system performance
- When consulting NetInfo, climbs from local domain to root domain



# Talking to NetInfo

- Through System Libraries and lookupd
- Primitive ONC-RPC protocol
- "C" client library
- Objective-C API (NIAccess framework)
- Integrated directory services API planned



## System Libraries

- gethostbyname(), getpwnam(), and etc.
- Limited set of categories (users, printers, hosts, etc.)
- Limited set of properties for each category—no data for nonstandard keys in NetInfo



## **ONC-RPC Protocol**

- Tedious in the extreme
- No documentation



## C Client Library

- Fairly simple open, search, read, write —style routines
- Data Structures galore
- On-line documentation



#### **NIAccess Framework**

- Objective-C API on top of C client library
- Classes for Domain, Directory, etc.
- On-line documentation



#### What Can I Do with NetInfo?

- Create new Network and System Administration applications and management utilities
- Reliable data store
- Location broker and rendezvous for network applications
- Extend existing data to support your code (e.g., "security\_clearance" property for a user)



## What Shouldn't I Do with NetInfo

- Poor performance on write operations
- Best performance for small (<=512 byte) records</li>

